

CEDAR LOVE SEAT with rounded top ASSEMBLY

G) Love Seat Back



H) Love Seat Base



I-R) Right Love Seat Arm/Leg Section



I-L) Left Love Seat Arm/Leg Section



A) Carriage Bolts
(10 @ 2 1/2", 2 @ 2")

B) Nuts (12)

C) Washers (12)

D) Lock Washers (12)



A



B



C



D

ASSEMBLY INSTRUCTIONS

Step 1. Place love seat base (H) on a non-marking surface.

Step 2. Attach front of right arm/leg section (I-R) to love seat base (H) by inserting 2 1/2" carriage bolt (A) into arm/leg section through the base and attach washer (C), then lock washer (D), then nut (B) and tighten.

Step 3. Repeat on the back of right arm/leg section.

Step 4. Repeat steps 2 and 3 to attach left arm/leg section (I-L).




Step 5. Slide love seat back (G) down into love seat base (H) with the brace under the last slat, lining up holes.



Step 6. Attach love seat back (G) to arm/leg section (I-R) by inserting 2 1/2" carriage bolts (A) into the top hole of the arm/leg section (I-R) and loosely attach washer (C), then lock washer (D), then nut (B).

Step 7. Repeat step 6 on left arm/leg section (I-L).



Step 8. Insert 2" carriage bolts (A) through the holes from the top side of the last slat of the love seat base (H) down through the chair back (G), then loosely attach washer (C), then lock washer (D), then nut (B).

Step 9. Tighten all hardware.



Assembled
Cedar Love Seat
With Rounded Top



www.TheBlueRooster.com
1-800-303-4312